

Fitting instructions

These instructions demonstrate how to fit all Generation 2 Hoselink Connectors. Please follow instructions to match the connectors your have purchased.

For further assistance, please **email** hello@hoselink.com.au or **call** 1300 900 617 (Monday to Friday 9am - 5pm AEST)

CONNECTOR TYPES

Hose End
Connctors



Proceed to
Step 1

Universal Tap
Conncteor



Proceed to
Step 2

Accessory
Connctors



Proceed to
Step 3

Adapters



Proceed to
Step 5

Step 1

Fit the Hose End Connectors


a. Prepare half a cup of boiling water



b. Ensure the hose is cut square



c. Slide grey nut on to hose & put white split ring flush with hose end.



d. **IMPORTANT!** Submerge the hose end 2cm deep into boiled water for approx. 10 seconds to soften.

e. 1 Pull the stem out of the connector body, place the stem on a hard flat surface & push the hose down firmly, ensuring hose and split ring are ALL the way to the bottom.




e. 2 Push the hose and stem back into the connector body, making sure the stem is fully inserted.



Tip: If the hose is not going all the way down, try spraying silicone lubricant onto the stem of the Hose End Connector and inside the hose.


f. Tighten the grey nut.



Step 2

Fit Tap Connector

Screw tightly on to the tap. If connector appears too small, unscrew size reducer and screw the main connectorbody on to the tap.



Step 3

Fit Accessory Connector

Screw directly into the Hoselink sprayer.



Step 4

Connecting it all together

Line up the 'lugs' on each fitting, then point and twist together until firmly locked. You should feel a slight click



Line up lugs and join together.

Twist to lock until you hear a 'click'.

Finished Product



TIPS ON USING HOSELINK

How to join hoses

This is easy, just connect one hose end to the other with a point and twist!



Troubleshooting

Please refer to our website for manuals and how-to videos:

www.hoselink.com.au/pages/support-product-support-connectors

Step 5

How to use Hoselink with an Adapter or convert them to Hoselink

To connect to your existing watering accessories, for best results, **DON'T** use an adapter!

Unscrew the click-on fitting and replace it with an appropriate Hoselink Connector.



Use a Universal Tap Connector (C2010BGAF) with most pressure washers.



Use an Accessory Connector (C2020BGAF) with watering accessories. You may find some products have a moulded or glued click-on fitting. If this is the case, you'll need a Click-on Adapter (2490).



This adapter allows you to connect to a click-on type fitting on one end and to a Hoselink Accessory Connector on the other.



For more information on how you can adapt to Hoselink, please visit: www.hoselink.com.au/pages/adapt-to-hoselink

My hose is skinny

If the wall of your hose is very thin and you are experiencing leaking, use secateurs to cut a further 2mm off the white split ring. This ensures the split ring can grip tightly around the hose.



How to remove a connector

Follow these steps: Unscrew the grey nut and remove the stem from the connector. Using a small screwdriver, place it in the gap on the split ring to leverage the ring open, and move it back up the hose. Submerge the hose and stem in boiling water for 10-15 seconds. Remove and drain off the water. Place the stem between your feet and pull firmly upwards on the hose to release it from the barbed stem.

