



MODEL: L338

Solar Path Lights with Glass Insert
Warm White | 2 Pack | SVELTE

For more information visit

hoselink.com.au

or call

1300 900 617

Cultivating **Connections**

 youtube.com/hoselink



User Manual

MODEL: L338

Solar Path Lights with Glass Insert
Warm White | 2 Pack | SVELTE

HOSELINK[®]

Kit Contents

- 2 x Solar Path Lights
- 2 x Ground Spikes
- 2 x Hardware Kit (2 x screws and 2 x masonry plugs)

Lighting Modes

- 100 lumens for the first 2 hours, then drops by 20 lumens per hour over the next 4 hours then stays on at 20 lumens until dawn.
- Produces 50 lumens of light constantly until dawn.

Activate the Light

STEP 1 Find a suitable location

Solar lights need access to direct sunlight for optimum results; preferably 6-8 hours per day.

STEP 2 Activate the lights

Press and hold the clear button on the underside of the solar light for 3 seconds to turn the light on and off. To change between lighting modes, press the clear button on the underside to select your desired setting:

Mode 1 - the red indicator will flash one time.

Mode 2 - the red indicator will flash 2 times.

Be sure to clean the solar panel periodically to maintain optimal performance.

Product Installation

STEP 1 Find a suitable location

Solar lights need access to direct sunlight for optimum results; preferably 6-8 hours per day.

STEP 2 Install the lights

Product Installation - Option A

Ground spike

A.1 Screw the ground spike into the base of the light and push the spike into the ground.

Product Installation - Option B

Using supplied hardware

- B.1** Using the light as a template, mark out screw holes with a marker pen.
- B.2** Drill the holes using a 6mm drill piece for masonry installation. Gently hammer the plug into place and then secure the screw tightly.

B.3 For timber, drill 3mm pilot holes to guide screws into place (plastic plugs are not required).

Storing the Lights

Manually switch the power to OFF. This will preserve the battery and prevent it from fully discharging during extended storage.

Specifications

Solar Panel	Monocrystalline silicon, 4.32V/ 1W
Lithium Battery	4.32V / 2000mAh
Operating Time	48 hours
Charge Time	8.7 hours
Replaceable Battery	Yes
LED Lumens	100 Lumens
Number of LEDs	4
Waterproof Rating	IP44
Recommended Mounting Height	Ground Mounted

WARNING: DO NOT USE THIS LIGHT UNDERWATER OR IN LOW-LYING PUDDLES.