



MODEL: 5532-WG
Root Waterer & Soil Breaker

For more information visit

hoselink.com.au

or call

1300 900 617

Cultivating **Connections**

 youtube.com/hoselink



User Manual

MODEL: 5532-WG
Root Waterer & Soil Breaker

HOSELINK[®]

Kit Contents

- 1 x Aluminium Tube
- 1 x Metal Trigger Handle with Brass Nut
- 1 x Hoselink Accessory Connector

The Hoselink Root Waterer & Soil Breaker is an environmentally friendly way to water large trees and shrubs, by delivering water directly to their roots underground, thereby reducing water evaporation. It is also useful to break up hard soil, making the removal of weeds or plants much easier.

Assembly Instructions

STEP 1 Unscrew the brass nut

Unscrew the fluted brass nut off the Metal Trigger Handle.

STEP 2 Insert Aluminum Tube

Slide the O-ring end of the Aluminium Tube into the handle, until it stops at the O-ring.

STEP 3 Secure with Brass Nut

Slide the brass nut over the pointed end of the Aluminium Pole and screw it onto the Metal Trigger Handle. This secures the pole to the handle.

STEP 4 Attach hose

Attach a Hoselink-fitted garden hose to the Accessory Connector.

Using the Root Waterer

Gently ease the end of the tube into the ground/soil and gradually depress trigger. Continue pushing the end of the tool into the ground. In addition to the large water outlet, there are small holes around the base of the Aluminum Pole to disperse water horizontally.

The tube will try to bury itself into the soil with little effort. If you meet hard resistance, such as a rock or tree root, stop immediately and try a different spot nearby.

Take care not to bend the Aluminium Tube or to force it into hard ground too quickly, as this may cause it to break.

For very hard ground, commence water pressure near the surface and allow the soil to soften before slowly increasing depth.

Storage & Maintenance

We recommend storing in the garage or shed when not in use. This will prolong the life of the product, protect it from the elements and prevent it from becoming a trip hazard in your garden.

The Metal Trigger Handle will need occasional lubrication with silicone oil or silicone spray to prevent the trigger plunger from sticking. With regular maintenance, this high quality metal product will provide you with years of reliable service.

12 month warranty.

